

Statistical Mechanics of an Urban Cross : A Solvable Model

M.Ebrahim Fouladvand^{1,3}, Masoud Nematollahi² and Farzad Zolfaghari²

¹ Department of Physics, Sharif University of Technology, P.O. Box 11365-9161, Tehran, Iran.

² Tehran Traffic Control Company (TTCC), P.O. Box 15836, Tehran, Iran.

³ Institute for Studies in Theoretical Physics and Mathematics, P.O. Box 19395-5531, Tehran, Iran.

(February 6, 2008)

We propose a model for the intersection of two urban streets. The traffic status of the crossroads is controlled by a set of traffic lights which periodically switch to red and green with a total period of T . Two different types of crossroads are discussed. The first one describes the intersection of two one-way streets, while the second type models the intersection of a two-way street with an one-way street. We assume that the vehicles approach the crossroads with constant rates in time which are taken as the model parameters. We optimize the traffic flow at the crossroads by minimizing the total waiting time of the vehicles per cycle of the traffic light. This leads to the determination of the optimum green-time allocated to each phase.

Over the past decade, the majority of the studies in the inter-disciplinary field " *physics of traffic* " have been allocated to the *highway traffic* (for a review see Ref. [1-3]) and less attention has been paid to the urban traffic. The simulation of traffic flow in a large-sized city is a formidable task and many degrees of freedom have to be involved (see e.g. [4]). In practice, streets of a city form a network of junctions that are linked together. Each crossroads receives demands (vehicles attempting to pass the cross) and at each crossroads there exists a traffic light which, with some certain programming, controls the transportation. The first model introduced by statistical physicists for the description of the city network which is known as the BML model in the literature, uses a deterministic cellular automata framework [5] and predicts a sort of phase transition from free-flow to a jammed state, but the model assumptions are too simple to be taken seriously for practical purposes. Later, a more serious model was introduced by Schadschneider and Chowdhury [6]. This model combines the BML model together with the Nagel-Schreckenberg model of highway traffic [7]. Despite its nice formulation, there are still a lot of simplifications which prevent it from being an *effective* and applicable model to a city network. The empirical mechanism by which the traffic lights are controlled is generally divided into two distinct methods : fixed time and real-time. In the fixed-time method, a fixed value of time is allocated to the traffic light as well as its sub-phase times. In the real-time method, which is becoming increasingly popular in great cities, the ensemble of crossroads are intelligently controlled by a central controller. The control mechanism is usually based on the concept of producing a kind of *green waves* between the crossroads. These waves interact with each other, and, if the passing demands are of high values, the green waves may have destructive effects on each other, and, hence, the concept of green wave may fail to be the final solution for optimizing the overall flow.

In this paper we aim to analyze a single crossroads in de-

tail in order to find a better insight to the problem of optimizing the total flow in cities. Our single crossroads is the result of the intersection of two perpendicular streets. In their simplest structure, these streets can each direct a one-way traffic flow. With no loss of generality, we take them as one-way South to North (S-N) and West to East (W-E) streets. Cars arrive at the south and the west entrances of the crossroads. Here we assume the arrival rates of the cars , i.e. the number of cars reaching the crossroads per second, are constant in time. Although from everyday driving experiences in cities, we know that these rates have fluctuations in the course of time; yet in definite time intervals , the assumption of the constant arrival rates could be justified at least on a average level. We take the arrival rates to be α_1 (for S-N cars) and α_2 (for the W-E cars) respectively. Also we denote the passing-rate of cars (number of cars passing the crossroads in the unit of time during the green-phase) by β_1 and β_2 . The period of the traffic lights is taken to be a definite value T which is assumed to remain constant in the time interval under consideration. The starting time of each cycle of the traffic light is at the moment which the light turns green for the S-N street. The S-N light remains green until T_1 . At T_1 the traffic lights turn red for the S-N street and simultaneously changes to green for the W-E street. This is the beginning of the second phase which continues from T_1 to T (end of one cycle). During Phase I ($0 \leq t \leq T_1$), the S-N cars can pass the crossroads northward and W-E cars are stopped for the red light. Over Phase II ($T_1 \leq t \leq T$), the S-N cars must wait behind the red light whilst the W-E cars are passing through the crossroads.

Now the basic question is how should traffic engineers adjust the value of T_1 in order to optimize the traffic flow throughout the intersection? Regarding the fact that drivers are identical human beings and with the assumption that the number of passengers of each car takes an equal average value for each direction, the optimization task is realized by minimizing the total waiting time of

the cars per cycle of the traffic lights. For this purpose, we introduce two quantities N_1 and N_2 which represent the number of cars stopping at the red lights in the red phases of the S-N and W-E streets respectively. Clearly N_1 and N_2 are functions of time and, in general, are divided into different lanes on the streets. For the first cycle of the steady time-interval (in which the arrival rate are taken to be constant) the following equations are easily written down:

$$N_1(T_1) = [N_1(0) + (\alpha_1 - \beta_1)T_1]\theta \quad (1)$$

$$N_2(T_1) = N_2(0)\theta + \alpha_2 T_1 \quad (2)$$

$$N_1(T) = [N_1(0) + (\alpha_1 - \beta_1)T_1]\theta + \alpha_1(T - T_1) \quad (3)$$

$$N_2(T) = [N_2(0)\theta + \alpha_2 T - \beta_2(T - T_1)]\theta \quad (4)$$

The θ symbols ensures the positiveness of the quantities in the brackets, i.e. the value of θ is one if the quantity in the bracket is positive and zero elsewhere. This limitation is dictated to us since, by definition, the quantities N_1 and N_2 can only take positive values.

We now define the Total Waiting Time (TWT) of the vehicles per cycle of the traffic lights. It is the total time wasted by the vehicles during their stop in the red phases. The TWT is sum of the sub-waiting times of each direction. Denoting the TWT and the sub waiting times by T^W , $T^{(W,1)}$ and $T^{(W,2)}$ respectively, the following equations could be written for the n -th cycle

$$T_{n \rightarrow n+1}^{(W,1)} = \frac{1}{2}\alpha_1(T - T_1)^2 + N_1(nT + T_1)(T - T_1) \quad (5)$$

$$T_{n \rightarrow n+1}^{(W,2)} = N_2(nT)T_1 + \frac{1}{2}\alpha_2 T_1^2 \quad (6)$$

In the above equations, one must take into account the fact that during the red phase of a street, not all the cars reaching the crossroads wait equally. The cars reaching the intersection just after the light goes red (unlucky drivers) have the most waiting time, while those reaching the crossroads just before the lights turns green (lucky drivers) spend no time waiting. This leads to an average factor $\frac{1}{2}$ in the above equations. The value of $N_2(0)$ refers to the number of the stopped cars in the W-E street just after the instant when the light turns red for the W-E cars (in the first cycle). Here two distinct situations are identified. In the first case, $N_2(0)$ is nearly zero which describes the situation when the W-E street is not crowded. The other case is $N_2(0) \geq 0$ which corresponds to the situation of heavy traffic in the W-E street. This means that even in the final stages of the green phase for the W-E direction, still there is a considerable number of W-E cars desiring to pass the cross eastwards. The same scenario goes with the value of $N_1(T_1)$, and, as we will see

in what follows, these different cases lead to different pre-descriptions of the optimization. Before investigating these cases in details, it should be mentioned that for the arbitrary values of the rates we do not have a periodical structure in the values of the N_1 and N_2 . This can be easily verified by comparing $N_1(T)$ and $N_2(T)$ with their values at $t = 0$ which implies that, in general, one has $N_i(0) \neq N_i(T)$ for $i = 1, 2$. Now let us discuss the situation where $N_1(T_1) = N_2(0) = 0$. This refers to a light traffic flow in both directions during the first cycle of the interval. One can easily check that if the following stability conditions $\alpha_2 T - \beta_2(T - T_1) \leq 0$ and $\alpha_1 T - \beta_1 T_1 \leq 0$ hold, Then we always have the similar conditions in the next cycles $N_1(nT + T_1) = N_2(nT) = 0$ where n denotes the number of the traffic light cycle. In this particular case which here after will be called State I, the TWT is independent of the cycle-number, and minimizing the TWT with respect to T_1 leads to the following equation:

$$T_1 = \frac{\alpha_1}{\alpha_1 + \alpha_2} T \quad (7)$$

this answer must be consistent with the stability conditions which leads to the constraints $\beta_2 \geq \alpha_1 + \alpha_2$ and $\beta_1 \geq \alpha_1 + \alpha_2$ among the rates. We now investigate a totally different situation i.e. a crowded crossroads. Supposing that the first cycle is characterized by the conditions $N_2(0), N_1(T_1) > 0$. one could easily verify that provided the relations $\alpha_1 > \beta_1$ and $\alpha_2 T > \beta_2(T - T_1)$ hold, we have a quasi-stationary condition in the next cycles i.e. $N_1(nT + T_1), N_2(nT) > 0$. In sharp contrast to the State I, (this state which will be referred to as the State II), the values of N_1 and N_2 would be functions of the cycle number. It can be shown that in the large cycle-number limit one has $T_{n \rightarrow n+1}^{(W,1)} \sim n(T - T_1)(\alpha_1 T - \beta_1 T_1)$ and $T_{n \rightarrow n+1}^{(W,2)} \sim nT_1(\alpha_2 T - \beta_2(T - T_1))$. We now minimize the TWT with respect to T_1 which leads to the following equation:

$$T_1 = \frac{\beta_1 + \beta_2 + \alpha_1 - \alpha_2}{2(\beta_1 + \beta_2)} T \quad (8)$$

the consistency of this solution with stability conditions yields the following constraints: $\alpha_1 > \beta_1$ and $\alpha_1 \beta_2 + 2\alpha_2 \beta_1 + \alpha_2 \beta_2 \geq \beta_1 \beta_2 + \beta_2^2$. Also positiveness of T_1 itself imposes the extra restriction $\alpha_1 - \alpha_2 < \beta_1 + \beta_2$. Next we consider the situation (State III) where in the first cycle of the traffic light, one has $N_1(T_1) = 0$ but $N_2(0) > 0$ this correspond to the situation in which the S-N street has a light traffic flow while the W-E street has a heavy one. The conditions for having these situations repeated in the next cycles are $\alpha_1 T - \beta_1 T_1 \leq 0$ and $\alpha_2 T - \beta_2(T - T_1) \geq 0$. In the large cycle-number limit, the minimizing of the TWT leads to the value

$$T_1 = \frac{\beta_2 - \alpha_2}{2\beta_2} T \quad (9)$$

It could be easily checked that the above solution is inconsistent with the stability conditions, and, hence, is not

acceptable as an optimization of traffic light. This inconsistency will remain in the final state (State IV) which is characterized by $N_1(nT + T_1) > 0$ and $N_2(nT) = 0$. In this case, the solution obtained by minimizing the TWT is again inconsistent with the stability conditions. In these last two states, one must numerically find the consistent minima. We next consider another more usual configuration of a crossroads. Here we let the vehicles move in the both directions on the S-N street but still the vehicles in the W-E street are restricted to move eastwards. This situation describes a one-way to two-way urban intersection. Here each cycle consists of three phases. In the first phase which lasts for $0 \leq t \leq T_1$, the traffic light is green for the S-N cars and red for the other two directions. During the second phase which starts at T_1 and finishes at T_2 , the traffic light is green for the N-S cars and red for the other two directions. In the final phase, which last for $T_2 \leq t \leq T$, the traffic light remains green for the W-E cars and red for the N-S as well as S-N directions. The entrance rates are taken to be α_1, α_2 and α_3 and we denote the passing rate by β_1, β_2 and β_3 for each direction respectively. The starting time of the cycles is chosen to be the moment at which the traffic light turns green for the S-N direction. Similar equations for the Vehicle-Numbers N_1, N_2 and N_3 could be written down and one in principle can evaluate the TWT in terms of these quantities. The exact form of the TWT strongly depends on the positiveness of the vehicle-numbers just after the traffic lights goes red for the respective direction. In the case under consideration, eight different possibilities can occur. Let us only discuss the most probable one which corresponds to the the following situation: $N_1(nT + T_1) = N_2(nT + T_2) = N_3(nT) = 0$ In this case the traffic status is light in each of the three directions. Following the same discussion made for the previous crossroads, it could be easily verified that the triple stability condition for the validity of the above assumptions are as follows: $\alpha_1 T - \beta_1 T_1 \leq 0$, $\alpha_2 T - \beta_2 (T_2 - T_1) \leq 0$ and $\alpha_3 T - \beta_3 (T - T_2)$. It can be shown that minimizing the TWT with respect to T_1 and T_2

leads to the following fixation of T_1, T_2

$$T_1 = T \frac{\alpha_1(\alpha_2 + \alpha_3) - \alpha_2\alpha_3}{\alpha_1(\alpha_2 + \alpha_3) + \alpha_2\alpha_3} \quad (10)$$

$$T_2 = T \frac{2\alpha_1\alpha_2}{\alpha_1(\alpha_2 + \alpha_3) + \alpha_2\alpha_3} \quad (11)$$

One directly observes that in the symmetric case of equal arrival rates, T_1 and T_2 take the expected values $\frac{T}{3}$ and $\frac{2T}{3}$ respectively. The other point which must be mentioned is that in this traffic status, T_1 and T_2 do not depend on the passing rates, and are solely determined by the arrival rates. The remaining seven status will be discussed elsewhere.

For comparison of our model to the empirical data, a time-series analysis on two of Tehran intersections were carried out. The central part of Tehran is under control

of the SCATS (*Sydney Coordinated Adaptive Traffic System*) that is an intelligent traffic controller system. The strategy followed by most of urban traffic control systems is based on establishing green-wave along the major streets of cities. We considered two different intersections. The first one which is located in Tehran downtown connects Valiasr St. to Takhtejamshid St. Both of these are one-way and major streets. The other crossroads connects Abbasabad St.(one-way) to Mahnaz St.(one-way). In contrast to the previous case, here the first street is a major while the second street is a minor one. The data set is provided by magnetic counting loops which are installed just before the pedestrian-line of each crossroads. The data were collected on second of July, 2000. The three following figures show a time-series of data for our major-to-minor crossroads.




Fig. 1: The cycle-ratio of green-time of Abbasabad street to the total period of the traffic light cycle. The numbers on the horizontal axes are the cycle number.




Fig. 2: The cycle-ratio of the passed vehicles (during the green phases) of Abbasabad street to Mahnaz street of each traffic light cycle. The numbers on the horizontal axis denote the cycle number.




Fig. 3: the above graph denotes the total number of passed vehicles (from both streets) during fifteen-minute time intervals. The lower graph shows the number of passed vehicles from Mahnaz street during fifteen-minute intervals.

As seen from the graphs, the cycle-ratio of the green time allocated to Abbasabad str. strongly fluctuates due to demand fluctuations received by the cross. In order to have a rough estimation of our model parameters, we considered a two-hour time interval between 12:30-14:30. We approximated the ratio of $\frac{\alpha_1}{\alpha_2}$ by the ration of the total number of vehicles which have passed through Abbasabad Str. to that number for Mahnaz Street. This yields the value $\frac{\alpha_1}{\alpha_2} = 0.35$. Putting this value into equation (7) yields $\frac{T_1}{T} = 0.74$. On the other hand the averaged value of the cycle-ratio of the green time of Abbasabad street over the two-hour period leads to result $\frac{T_1}{T} = 0.64$. The following figures belong to our major-to-major crossroads.




Fig. 4: the cycle-ratio of green time allocated to Takhtejamshid Street. The numbers on the horizontal axis denote the cycle number.




Fig. 5: cycle-ratio of the passed vehicles from Takhtejamshid street to Valiasr street.




Fig. 6: the above graph denotes the total number of passed vehicles (from both streets) during fifteen-minute time intervals. The lower graph shows the number of passed vehicles from Takhtejamshid str. during fifteen-minute intervals. Here we focused on the interval 13:30 - 15:30. The averaged value of $\frac{T_1}{T}$ is 0.52 while the same amount evaluated from eq.(7) is 0.56.

In conclusion, we have developed a prescription for the traffic-light programming at a single urban crossroads. The method is based on minimizing the TWT of cars stopping in the red phases of the traffic light. The value of T should be so tuned that during the green phases, time-headway is less than a certain value. In fact, in the model the values of the passing rate refer to the maximum capacity of cross (maximum number of cars passing the cross in the unit of time), which is plausible if the T is appropriately adjusted with the congestion of the crossroads. Optimizing the traffic at each crossroads is the stating point of the more comprehensive problem of city network. Nevertheless, our model best suits those marginal intersections of cities where the effect of the other crossroads is suppressed.

Acknowledgments: M.E.F is grateful to *Tehran Traffic Control Company* for the data support. We would like to express our gratitude to R. Sorfleet, M.Arab salmani, M. Salmani and M. Khoshechin for useful helps.

-
- [1] Chowdhury, D., Santen, L., and Schadschneider, A., *Physics Reports*, **329**, 199 (2000).
 - [2] D.E Wolf and M. Schreckenberg (eds.) *Traffic and granular flow* (Springer, Singapore, 1998).
 - [3] H.J. Herrmann, D. Helbing, M. Schreckenberg and D.E. Wolf (eds.) *Traffic and Granular flow* (Springer, Berlin, 2000).
 - [4] *Traffic Flow Fundamentals*, Prentice Hall (1990) by A.D. May. *Transportation and Traffic Theory*, Elsevier (1993) by C.F Daganzo.
 - [5] O. Biham, A. Middleton and D. Levine, *Phys.Rev.* **A 46**, R6124 (1992).
 - [6] D. Chowdhury and A. Schadschneider, *Phys.Rev* **E 59**, R 1311 (1999).
 - [7] K.Nagel, M.Schreckenberg, *J.Phys.I France***2**, 2221(1992).